



MTHG Underlayment Screw



The MTHG underlay screw is designed for fast and secure underlayment to subfloor installations. Unlike nails, the MTHG Underlayment screw has an intricate thread pattern designed to prevent squeaking by holding underlayment tight to the subfloor and thus preventing pull-out. Its compact trim-head allows for a flush surface and prevents floor coverings from settling in countersink recesses.

Features

- Trim head with nibs for easy countersinking
- #2 square drive (driver bit in each box; replacement bit model BIT2S)
- High-low threads
- Sharp point
- Curved collation

Application


- Timber underlay to timber and steel
- Maximum recommended board thickness 9 mm
- Recommended steel thickness 0.55–0.75 mm

Finish

- Class 3 Galvanised



Trim head with nibs for easy countersinking



High-Low threads for secure holding down of underlayment to timber and steel frame

Collated Screws for the Quik Drive® System

7 Gauge Underlayment Screw

Bit(s) included with every box of screws

Model No.	Diameter	Length	Thread	Point	Box Qty	Drive Size	Replacement Bit	PRO 200	PRO 250	PRO 300
MTHG114SA	4.0mm	32mm	Hi-Lo Threads	Sharp	2500	#2 Square	BIT2S-RC10	✓	—	—

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. See pages 20–26 for additional important information before selecting a fastener for a specific application.