

# S&P Resin 55HP Component B

## SAFETY DATA SHEET

This Safety Data Sheet was prepared following the Code of Practice: Preparation of Safety Data Sheets for Hazardous Chemicals from Work Safe Australia and the New Zealand Code of Practice for the Preparation of Safety Data Sheets (SDS) [No. HSNO CoP 8-1 09-06]. This product has been classified according to the hazard criteria of the Globally Harmonized System (GHS) and contains all of the information required by Safe Work Australia and Work Safe New Zealand.

### 1. Identification

#### Product Identification

**Product Identifier:** S&P Resin 55HP Component B  
**Recommended Use:** S&P Resin 55HP Component B is a hardener for epoxy resin.  
**Use Restrictions:** To ensure proper installation use according to package directions, complete application instructions can be found in Simpson Strong-Tie catalogs or online at [strongtie.com](http://strongtie.com).

#### Company Identification

**Company:** Simpson Strong-Tie Australia Pty Limited  
**Address:** 2A/201 Power Street  
Glendenning, NSW 2761  
Australia  
**Phone:** 1300 787 664  
**Website:** [www.strongtie.com.au](http://www.strongtie.com.au)  
**Emergency:** 13 11 26

**Company:** Simpson Strong-Tie New Zealand  
**Address:** 52A Arrenway Drive  
Albany, Auckland 0632  
New Zealand  
**Phone:** +64 9 477 4440  
**Website:** [www.strongtie.co.nz](http://www.strongtie.co.nz)  
**Emergency:** 0800 POISON (0800 764 766)

### 2. Hazard Identification

#### General Information

S&P Resin 55 HP Part A and B is a high performance, solvent free, two-component, high-strength, high-modulus, epoxy resin adhesive used to saturate S&P sheet fabrics and prime substrates. This product has been assessed according to the Globally Harmonized System (GHS). Some hazards may apply upon grinding or cutting through hardened product. This Safety Data Sheet covers the hazards and responses for the safe use of this product.

#### GHS Classification

##### Classification according to HazCom2012 (GHS)

<b>Physical Hazards:</b>	Not Classified.		
<b>Health Hazards:</b>	Acute Toxicity, Oral	Category 4	H302: Harmful if swallowed
	Skin Corrosion/Irritation	Category 1	H314: Causes severe skin burns and eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
<b>Environmental Hazards:</b>	STOT, Repeated Exposure	Category 2	H373: May cause damage to organs through prolonged or repeated exposure
	Chronic Aquatic Hazard	Category 3	H412: Harmful to aquatic life with long lasting effects

**Main Symptoms:** Causes severe skin burns and eye damage. Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure. May cause an allergic skin reaction. Occupational exposure to the substance or mixture may cause adverse health effects.

#### GHS Label Elements



**Contains:** 2,4,6-Tris-(dimethylaminomethyl)phenol, 4,4'-Methylenebis(cyclohexylamine), Benzyl alcohol, Copolymer of benzenamine and formaldehyde, hydrogenated, Poly(oxypropylene)diamine

**Signal Word:** DANGER!

**Hazard Statements:** H302: Harmful if swallowed.  
H314: Causes severe skin burns and eye damage.  
H317: May cause an allergic skin reaction.

# S&P Resin 55HP Component B

## SAFETY DATA SHEET



	H373:	May cause damage to organs (liver, muscle) through prolonged or repeated exposure.
	H412:	Harmful to aquatic life with long lasting effects.
<b>Precautionary Statements:</b>		
<b>Prevention:</b>	P102:	Keep out of reach of children.
	P103:	Read label before use.
	P202:	Do not handle until all safety precautions have been read and understood.
	P260:	Do not breathe dust, mist, or vapor.
	P264:	Wash thoroughly after handling.
	P270:	Do not eat, drink, or smoke when using this product.
	P272:	Contaminated clothing should not be allowed out of the workplace.
	P273:	Avoid release to the environment.
	P280:	Wear protective gloves/protective clothing/eye protection/face protection.
<b>Response:</b>	P301+P330+P331:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P310:	Immediately call a POISON CENTER/doctor.
	P303+P361+P353:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P363:	Wash contaminated clothing before reuse.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P308+P313:	If exposed or concerned: Get medical advice/attention.
	P391:	Collect spillage.
<b>Storage:</b>	P405:	Store locked up.
<b>Disposal:</b>	P501:	Dispose of contents/container in accordance with local/regional regulations.

**Supplemental Label Information:** EUH205 - Contains epoxy constituents. May produce an allergic reaction.

### 3. Composition Information

#### General Information

This product is a mixture. Hazardous ingredients for Component B are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

#### List of abbreviations and symbols:

Classification: Globally Harmonized System Classifications

The full text for H- phrases is displayed in section 16. All concentrations are in percent by weight unless otherwise noted.

**Composition- All compositions are in percent by weight unless otherwise indicated.**

Chemical Name	Weight %	CAS Number	EC Number
Poly(oxypropylene)diamine <b>Classifications:</b> Skin Corr. 1B: H314, Eye Corr. 1: H318, Aquatic Chronic 3: H412	50-100	9046-10-0	-
4,4'-Methylenebis(cyclohexylamine) <b>Classifications:</b> Acute Tox. 4: H302, Skin Corr. 1B: H314, Skin Sens. 1: H317, Eye Corr. 1: H318, STOT RE 2: H373	10-25	1761-71-3	217-168-8
Benzyl alcohol <b>Classifications:</b> Acute Tox. 4: H302, Eye Irrit. 1: H319	10-25	100-51-6	202-859-9
2,4,6-tris-(dimethylaminomethyl)phenol <b>Classifications:</b> Acute Tox. 4: H302, Skin Corr. 1B: H314, Eye Corr. 1: H318, Aquatic 3: H402	2.5-10	90-72-2	202-013-9
Colpolymer of benzenamine and formaldehyde, hydrogenated <b>Classifications:</b> Acute Tox. 4: H302, Skin Corr. 1B: H314, Eye Corr. 1: H318, STOT RE 2: H373, Aquatic 3: H402	2.5-10	135108-88-2	-

### 4. First-Aid Measures

#### General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

#### Routes of Exposure

# S&P Resin 55HP Component B

## SAFETY DATA SHEET

<b>Eye Contact:</b>	Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, <b>consult a physician immediately.</b>
<b>Skin Contact:</b>	Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or poison control centre immediately. Chemical burns must be treated <b>by a physician.</b> Wash contaminated clothing before reuse.
<b>Ingestion:</b>	Rinse mouth immediately. Do not induce vomiting unless told to do so by a poison control center or doctor. If vomiting occurs keep head low so that stomach contents don't get into the lungs. Never give anything by mouth to an unconscious person. <b>Consult a physician immediately.</b>
<b>Inhalation:</b>	If breathing is difficult remove patient to fresh air and keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, <b>consult a physician.</b>

### Most Important Symptoms

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects. Sensitization.

### 5. Fire-Fighting Measures

<b>Suitable Extinguishing Media:</b>	Extinguish with foam, carbon dioxide, dry powder, or water fog.
<b>Additional Information:</b>	Do not use water jet as an extinguisher as this will spread the fire.
<b>Hazards during Fire-Fighting:</b>	Hazardous decomposition products may occur when materials polymerize at temperatures above 500° F (260°C). Irritating and toxic gases/fumes may be released during a fire. Do not allow run-off from fire-fighting to enter drains or water courses.
<b>Fire-Fighting Procedures:</b>	Use standard firefighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out.
<b>Combustion Products:</b>	In combustion emits toxic fumes.

### 6. Accidental Release Measures

#### Personal Precautions

**Non-emergency personnel:** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

**Emergency personnel:** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

#### Clean-Up Methods

<b>Small spills (uncured):</b>	Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination. If desired, approved solvents, such as ketones (MEK, acetone, etc.), lacquer thinner, or adhesive remover can be used. Do NOT use solvents to clean adhesives from skin. Take appropriate precautions when handling flammable solvents. Solvents may damage surfaces to which they are applied.
<b>Large spills (uncured):</b>	Stop the flow of material, if this is without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water. Keep combustibles away from spilled material.
<b>Cured Material:</b>	Chip or grind off surface. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust. Take precautionary measures; do not allow dust to build up.

#### Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and Storage

#### Handling

# S&P Resin 55HP Component B

## SAFETY DATA SHEET

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flame, hot surfaces, and sources of ignition. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Do not breathe dust, mist or vapor. Use only in well-ventilated places. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. To obtain optimal performance from Simpson Strong-Tie products and to achieve maximum allowable design load, the products must be properly installed and used in accordance with the installation instructions and design limits provided by Simpson Strong-Tie.

### Storage

Keep away from incompatible materials. Keep in original container. Keep container tightly closed. Store in a dry, well-ventilated place out of direct sunlight. Keep away from heat and sources of ignition. Protect container from physical damage. Avoid freezing temperatures. Keep out of reach of children.

## 8. Exposure Controls / Personal Protection

### Personal Protective Equipment

**Protective Measure:** Wear appropriate protective equipment.  
**Eye Protection:** Chemical splash goggles or safety glasses with side shield are recommended.  
**Hand Protection:** Wear chemical-resistant gloves such as: Nitrile, neoprene, or butyl rubber.  
**Skin and Body Protection:** Wear long sleeve shirt/long pants and other clothing as required to minimize skin contact.  
**Respirator Protection:** If engineering controls do not maintain airborne concentrations below recommended exposure limits, or if discomfort is experienced, an approved respirator should be worn.  
**General Hygiene:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### Engineering Controls

Mechanical ventilation or local exhaust ventilation is recommended. Ventilation rates should be matched to conditions to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and emergency shower.

### Exposure Limits

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Benzyl Alcohol (CAS 100-51-6)	5 mg/m <sup>3</sup> (respirable) 15 mg/m <sup>3</sup> (total dust)	10 mg/m <sup>3</sup> (TWA)	N/E

## 9. Physical and Chemical Properties

### Property

**Physical State:** Liquid, Viscous  
**Color:** Transparent  
**Odor:** No data  
**pH:** No data  
**Flammability limit – lower %:** No data  
**Flammability limit – upper %:** No data  
**Vapor Pressure:** No data  
**Vapor Density:** No data  
**Solubility:** Insoluble in water  
**Freezing/Melting Point:** No data  
**Boiling Point:** No data  
**Flash Point:** >93.3C (>199.9°F)  
**Evaporation Rate:** No data  
**Decomposition Temperature:** No data  
**Relative Density:** 1.02  
**VOC:** < 3%  
**Viscosity:** 100 mPa\*s (20°C)

## 10. Stability and Reactivity

### Component B

**Reactivity:** This product is stable and non-reactive under normal conditions of use, storage, and transport.

# S&P Resin 55HP Component B

## SAFETY DATA SHEET

**Chemical Stability:** Stable under normal conditions.  
**Condition to Avoid:** Heat and open flame. Contact with incompatible materials.  
**Substances to Avoid:** Acids. Metals. Oxidizing Agents.  
**Hazardous Reactions:** No dangerous reactions known under conditions of normal use.  
**Decomposition Products:** No hazardous decomposition products are known. Thermal decomposition or combustion may produce: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Ammonia.

### 11. Toxicological Information

#### Likely Routes of Exposure

**Ingestion:** Harmful if swallowed. Causes digestive tract burns.  
**Inhalation:** Inhalation of vapors or mists of the product may be irritating to the respiratory system.  
**Skin contact:** Causes severe skin burns. May cause an allergic skin reaction.  
**Eye contact:** Causes serious eye damage.  
**Symptoms:** Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Sensitization.

#### Information on Toxicological Effects

##### Acute Effects

**Toxicity:** Harmful if swallowed.

Chemical	Estimate
S&P Resin 55HP Component B Toxicity Estimate	
<b>Acute, Oral, LD50</b>	2100 mg/kg
<b>Acute, Dermal, LD50</b>	> 2000 mg/kg

**Skin corrosion/irritation:** Causes severe skin burns.  
**Eye damage/eye irritation:** Causes serious eye damage.  
**Respiratory sensitization:** No data available.  
**Skin sensitization:** May cause an allergic skin reaction.  
**Aspiration hazard:** No data available.  
**Specific target organ toxicity:**  
**Single exposure** No data available.

##### Chronic Effects

**Germ cell mutagenicity:** No data available.  
**Carcinogenicity:** No data available.  
**Reproductive toxicity:** No data available.  
**Specific target organ toxicity:**  
**Repeated exposure** May cause damage to organs (liver, muscle) through prolonged or repeated exposure.

#### Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

### 12. Ecological Information

#### General Information

Information given is based on the components and the ecotoxicity of similar products. S&P Resin 55HP Component B is classified as harmful to aquatic life with long-lasting effects. Avoid release to the environment.

#### Supporting Data

Component	Estimate
S&P Resin 55HP Component B Toxicity Estimate	
<b>Aquatic, Fish, LC50</b>	60 mg/l, 96 hours
<b>Aquatic, Daphnia magna, EC50</b>	15 mg/l, 48 hours

**Persistence and degradability:** No data available.  
**Bioaccumulative potential:** No data available for this product.

# S&P Resin 55HP Component B

## SAFETY DATA SHEET

Mobility in soil: No data available.

### Further Information

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

### 13. Disposal Consideration

**Waste Disposal of Substance:** Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

**Container Disposal:** Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**Disposal of Cured Product:** Chip or grind off surface. Solid material does not need special disposal consideration.

### 14. Transportation Information

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

<b>UN number:</b>	UN2735
<b>UN proper shipping name:</b>	AMINES, LIQUID, CORROSIVE, N.O.S. (Poly(oxypropylene)diamine, 4,4'-Methylenebis(cyclohexylamine)), 8, II
<b>Transportation Class:</b>	8
<b>Packing Group:</b>	II
<b>Environment Hazard:</b>	No
<b>Required Labels:</b>	8
<b>ERG Code (IATA):</b>	8L
<b>EmS (IMDG):</b>	F-A, S-B
<b>Special Precautions for Users:</b>	Ready safety instructions, SDS and emergency procedures before handling.

Based on packaging size, Limited Quantity exemptions may apply. Please consult the 49 CFR HMR, IATA DGR, and IMDG Code to ensure that shipments comply with these regulations.

### Additional Information

**Special precautions for user:** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not intended to be transported in bulk

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

### 15. Regulatory Information

#### United States

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA):

Hazard Categories:	Immediate	Delayed	Fire	Pressure	Reactivity
Hardener	Yes	Yes	No	No	No

**SARA 302 Extremely hazardous substance:** None.

**SARA 311/312 Hazardous chemical:** Yes

**SARA 313 (TRI reporting):** None.

#### Canada

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

#### European Union

The product is classified in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

# S&P Resin 55HP Component B

## SAFETY DATA SHEET

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

### International Inventories

<b>Australia</b>	One or more components of this product have an unknown status on the Australian Inventory of Chemical Substances (AICS).
<b>Canada</b>	All components of this product are included on the Domestic Substances List (DSL).
<b>China</b>	One or more components of this product have an unknown status on the Inventory of Existing Chemical Substances in China (IECSC).
<b>Europe</b>	One or more components of this product have an unknown status on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are exempt from listing.
<b>Japan</b>	One or more components of this product have an unknown status on the Inventory of Existing and New Chemical Substances (ENCS).
<b>Korea</b>	One or more components of this product have an unknown status on the Existing Chemicals List (ECL).
<b>New Zealand</b>	One or more components of this product have an unknown status on the New Zealand Inventory. Contact Simpson Strong-Tie Environmental Health and Safety if the status of this product on the inventory is desired.
<b>Philippines</b>	One or more components of this product have an unknown status in the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
<b>United States</b>	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.

### 16. Other Information

**Date Prepared or Revised:** December 2022  
**Supersedes:** August 2022  
**Contact Simpson Strong-Tie Environmental Health and Safety at [EHS@strongtie.com](mailto:EHS@strongtie.com)**

### Abbreviations

<b>ACGIH:</b>	American Conference of Governmental Industrial Hygienists
<b>CAS No.:</b>	Chemical Abstract Service Registry Number
<b>CERCLA:</b>	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
<b>HPR:</b>	Hazardous Product Regulations (Canada)
<b>DOT:</b>	Department of Transportation (U.S.)
<b>EPA:</b>	Environmental Protection Agency (U.S.)
<b>GHS:</b>	Globally Harmonized System of Classification and Labeling of Chemicals
<b>HEPA:</b>	High-Efficiency Particulate Air
<b>HMIS:</b>	Hazardous Materials Identification System
<b>IARC:</b>	International Agency for Research on Cancer
<b>IATA:</b>	International Air Transport Association
<b>IMDG:</b>	International Maritime Dangerous Goods code
<b>NIOSH:</b>	National Institute of Occupational Safety and Health (U.S.)
<b>NFPA:</b>	National Fire Protection Association (US)
<b>NTP:</b>	National Toxicology Program (US)
<b>OSHA:</b>	Occupational Safety and Health Administration (U.S.)
<b>PEL:</b>	Permissible Exposure Limit
<b>SARA:</b>	Superfund Amendments and Reauthorization Act (U.S. EPA)
<b>STEL:</b>	Short Term Exposure Limit (15 minute Time Weighted Average)
<b>STOT:</b>	Specific Target Organ Toxicity (GHS Classification)
<b>TLV:</b>	Threshold Limit Value
<b>TSCA:</b>	Toxic Substances Control Act (U.S.)
<b>TWA:</b>	Time Weighted Average (exposure for 8-hour workday)
<b>VOC:</b>	Volatile Organic Compounds
<b>WHMIS:</b>	Canadian Workplace Hazardous Materials Information System

Full Text of H – Phrases Under Section 3

# S&P Resin 55HP Component B

## SAFETY DATA SHEET



H318: Causes serious eye damage.  
H319: Causes serious eye irritation.  
H402: Harmful to aquatic life.

### Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2022 Simpson Strong-Tie Company Inc.