

# EP-XP — Extreme Performance Pure Epoxy

## Material

- Pure Epoxy

## Construction Types

- Commercial Construction
- Residential Construction

## Features and Benefits

- Suitable for use in cracked and non-cracked concrete M8 to M30 / rebar Ø8 to Ø40
- Extreme Performance for structural applications with high loads, ideal for commercial use
- Qualified for use in seismic performance categories C1 and C2
- Slow cure formulation ideal for deeper embedments
- Can be used in dry and damp conditions, wet or flooded environments (not sea water)
- 100 Years Working Life
- Fire rating R120
- VOC Compliant (A+ rating)
- Styrene Free
- NSF Certified (drinking water)

## Applications

- Post-installed Rebar
- Threaded Rod Anchoring
- Structural Steel
- Steel Columns and Beams, Post Bases, Concrete Columns
- Balcony Extensions
- Facades, Safety Barriers
- Fences, Gates, Industrial Garage and Warehouse applications


## Base Material

- Cracked and non-cracked concrete, light-concrete, porous-concrete, solid masonry, hollow brick, natural stone, wood

## Approvals



SCAN FOR MORE INFO



Australia

New Zealand

## EP-XP Curing Schedule – Maximum working time and minimum curing time

| Temperature of Concrete | Working Time  | Curing Time* |
|-------------------------|---------------|--------------|
| 0°C to +4°C             | 90 min        | 144 h        |
| +5°C to +9°C            | 80 min        | 48 h         |
| +10°C to +14°C          | 60 min        | 28 h         |
| +15°C to +19°C          | 40 min        | 18 h         |
| +20°C to +24°C          | 30 min        | 12 h         |
| +25°C to +34°C          | 12 min        | 9 h          |
| +35°C to +39°C          | 8 min         | 6 h          |
| +40°C                   | 8 min         | 4 h          |
| Cartridge temperature   | +5°C to +40°C |              |

\*In wet concrete the curing times must be doubled

**Simpson Strong-Tie® (New Zealand) Ltd**

**Call 09 477 4440**

**www.strongtie.co.nz**

**Simpson Strong-Tie® Australia Pty Ltd**

**Call 1300 STRONGTIE (1300 787 664)**

**www.strongtie.com.au**

**Simpson Strong-Tie Limited Warranty:** For the Limited Warranty that applies to Simpson Strong-Tie products, please consult [www.strongtie.com.au/warranty](http://www.strongtie.com.au/warranty) or [www.strongtie.co.nz/warranty](http://www.strongtie.co.nz/warranty). To obtain a copy of the Limited Warranty, contact us at [info.au@strongtie.com](mailto:info.au@strongtie.com) or [info.nz@strongtie.com](mailto:info.nz@strongtie.com), or at the number provided here. The Limited Warranty contains important disclaimers, limitations and exclusions, and applies only if the products have been properly specified, installed, maintained, and used in accordance with the design limits and the structural, technical, and environmental specifications in the Simpson Strong-Tie Documentation. All future purchases of Simpson Strong-Tie products are subject to the terms of the Limited Warranty in effect as of the purchase date. This flyer reflects information available as of May 2025 and may be updated periodically.



# EP-XP — Extreme Performance Pure Epoxy

**Table 1: EP-XP Pure Epoxy Installation Parameters - Gr 8.8 Threaded Rod**

| Description                        | Symbol                     | Units | Threaded Rod Size (mm)          |     |                  |                                   |     |     |     |     |
|------------------------------------|----------------------------|-------|---------------------------------|-----|------------------|-----------------------------------|-----|-----|-----|-----|
|                                    |                            |       | M8                              | M10 | M12              | M16                               | M20 | M24 | M27 | M30 |
| Nominal Insert Diameter            | d                          | mm    | 8                               | 10  | 12               | 16                                | 20  | 24  | 27  | 30  |
| Drill Hole Diameter                | d <sub>o</sub>             |       | 10                              | 12  | 14               | 18                                | 22  | 28  | 30  | 35  |
| Minimum Embedment Depth            | h <sub>ef,min</sub>        |       | 60                              | 60  | 70               | 80                                | 90  | 96  | 108 | 120 |
| Maximum Embedment Depth            | h <sub>ef,max</sub>        |       | 160                             | 200 | 240              | 320                               | 400 | 480 | 540 | 600 |
| Clearance Hole Diameter in Fixture | Prepositioned installation |       | 9                               | 12  | 14               | 18                                | 22  | 26  | 30  | 33  |
|                                    | Push through installation  |       | 12                              | 14  | 16               | 20                                | 24  | 30  | 33  | 40  |
| Installation Torque                | T <sub>inst, max</sub>     | Nm    | 10                              | 20  | 40 <sup>1)</sup> | 60                                | 100 | 170 | 250 | 300 |
| Minimum Concrete Thickness         | h <sub>min</sub>           | mm    | h <sub>ef</sub> + 30mm (≥100mm) |     |                  | h <sub>ef</sub> + 2d <sub>o</sub> |     |     |     |     |
| Minimum Edge Distance              | c <sub>min</sub>           |       | 35                              | 40  | 45               | 50                                | 60  | 65  | 75  | 80  |
| Minimum Spacing                    | s <sub>min</sub>           |       | 40                              | 50  | 60               | 75                                | 95  | 115 | 125 | 140 |

1) Maximum installation torque for M12 with steel Grade 4.6 is 35 Nm.

**Table 2: EP-XP Pure Epoxy - Design Resistance - Single Anchor, No Concrete Edge or Spacing Influence, 100 years working life**

| Description                | Symbol    | Units | M8   | M10  | M12  | M16  | M20  | M24   | M27   | M30   |
|----------------------------|-----------|-------|------|------|------|------|------|-------|-------|-------|
| Embedment Depth            | $h_{ef}$  | mm    | 70   | 80   | 110  | 140  | 180  | 220   | 300   | 450   |
| Minimum Concrete Thickness | $h_{min}$ |       | 100  | 110  | 140  | 176  | 224  | 276   | 360   | 520   |
| NON-CRACKED CONCRETE       |           |       |      |      |      |      |      |       |       |       |
| TENSION                    | $N_{Rd}$  | kN    | 18.2 | 23.6 | 42.3 | 60.7 | 88.5 | 119.6 | 190.5 | 299.3 |
| SHEAR                      | $V_{Rd}$  |       | 12   | 18.4 | 27.2 | 50.4 | 78.4 | 112.8 | 147.2 | 179.2 |
| CRACKED CONCRETE           |           |       |      |      |      |      |      |       |       |       |
| TENSION                    | $N_{Rd}$  | kN    | 6.9  | 10.5 | 23.5 | 39.8 | 61.9 | 83.7  | 133.3 | 240.3 |
| SHEAR                      | $V_{Rd}$  |       | 12   | 18.4 | 27.2 | 50.4 | 78.4 | 112.8 | 147.2 | 179.2 |
| SEISMIC C1 CATEGORY        |           |       |      |      |      |      |      |       |       |       |
| TENSION                    | $N_{Rd}$  | kN    | 6.9  | 10.5 | 23.5 | 36.1 | 52.6 | 71.1  | 113.3 | 208.2 |
| SHEAR                      | $V_{Rd}$  |       | 8.4  | 12.9 | 19   | 35.3 | 54.9 | 79    | 103   | 125.4 |
| SEISMIC C2 CATEGORY        |           |       |      |      |      |      |      |       |       |       |
| TENSION                    | $N_{Rd}$  | kN    | -    | -    | 16   | 22.5 | 37.7 | 56.4  | 81.4  | 141.3 |
| SHEAR                      | $V_{Rd}$  |       | -    | -    | 19   | 35.3 | 54.9 | 79    | 103   | 125.4 |

1) Concrete strength is C20/25, f<sub>ck</sub>,cube = 25 N/mm<sup>2</sup> unreinforced, hammer drilling (HD) and CD, hole condition is "dry", temperature range 24°C long-term/40°C short-term.

2) Tabulated loads are valid at critical spacing and critical edge distance only.

3) N<sub>Rd</sub> and V<sub>Rd</sub> is based on use of a Grade 8.8 threaded insert. Verify capacity if using a different steel grade.

4) All design resistances are derived from the product's ETA (European Technical Assessment ETA-25/0483). For combined tension and shear loads or anchor groups, spacing and edge distance influence, a calculation per EAD 330499 shall be done. Simpson Strong-Tie® Anchor Designer™ for Concrete Software used for analysis.

5) Tabulated loads for C1 category are for a working life of 50 years.

6) Factor for annular gap a = 1.0

**Table 3: EP-XP Pure Epoxy - Steel Design Resistance (Tension)**

| Description                              | Symbol            | Units | M8          | M10         | M12  | M16  | M20   | M24   | M27   | M30   |
|------------------------------------------|-------------------|-------|-------------|-------------|------|------|-------|-------|-------|-------|
| Steel Grade 8.8 <sup>1)</sup>            | N <sub>Rd,s</sub> | kN    | 19.3 (18.0) | 30.7 (28.7) | 44.7 | 83.3 | 130.7 | 188.0 | 245.3 | 299.3 |
| Stainless Steel A2, A4 and HCR, Class 70 |                   |       | 13.9        | 21.9        | 31.6 | 58.8 | 91.4  | 132.1 | -     | -     |

1) Values in brackets are valid for undersized threaded rods with smaller stress area As for hot-dip galvanised threaded rods according to EN ISO 10684:2004+AC:2009

**Table 4: EP-XP Pure Epoxy - Steel Design Resistance (Shear without lever arm)**

| Description                              | Symbol            | Units | M8          | M10         | M12  | M16  | M20  | M24   | M27   | M30   |
|------------------------------------------|-------------------|-------|-------------|-------------|------|------|------|-------|-------|-------|
| Steel Grade 8.8 <sup>1)</sup>            | N <sub>Rd,s</sub> | kN    | 12.0 (10.4) | 18.4 (16.8) | 27.2 | 50.4 | 78.4 | 112.8 | 147.2 | 179.2 |
| Stainless Steel A2, A4 and HCR, Class 70 |                   |       | 8.3         | 12.8        | 19.2 | 35.3 | 55.1 | 79.5  | -     | -     |

1) Values in brackets are valid for undersized threaded rods with smaller stress area As for hot-dip galvanised threaded rods according to EN ISO 10684:2004+AC:2009

**Simpson Strong-Tie® (New Zealand) Ltd**

**Call 09 477 4440**

**www.strongtie.co.nz**

**Simpson Strong-Tie® Australia Pty Ltd**

**Call 1300 STRONGTIE (1300 787 664)**

**www.strongtie.com.au**

**Simpson Strong-Tie Limited Warranty:** For the Limited Warranty that applies to Simpson Strong-Tie products, please consult [www.strongtie.com.au/warranty](http://www.strongtie.com.au/warranty) or [www.strongtie.co.nz/warranty](http://www.strongtie.co.nz/warranty). To obtain a copy of the Limited Warranty, contact us at [info.au@strongtie.com](mailto:info.au@strongtie.com) or [info.nz@strongtie.com](mailto:info.nz@strongtie.com), or at the number provided here. The Limited Warranty contains important disclaimers, limitations and exclusions, and applies only if the products have been properly specified, installed, maintained, and used in accordance with the design limits and the structural, technical, and environmental specifications in the Simpson Strong-Tie Documentation. All future purchases of Simpson Strong-Tie products are subject to the terms of the Limited Warranty in effect as of the purchase date. This flyer reflects information available as of May 2025 and may be updated periodically.

# EP-XP — Extreme Performance Pure Epoxy

Table 5: EP-XP Pure Epoxy - Rebar

| Description                | Symbol              | Units | Rebar Size                      |                   |                   |     |     |                                   |                   |                   |     |     |
|----------------------------|---------------------|-------|---------------------------------|-------------------|-------------------|-----|-----|-----------------------------------|-------------------|-------------------|-----|-----|
|                            |                     |       | Ø8 <sup>1)</sup>                | Ø10 <sup>1)</sup> | Ø12 <sup>1)</sup> | Ø14 | Ø16 | Ø20                               | Ø24 <sup>1)</sup> | Ø25 <sup>1)</sup> | Ø28 | Ø32 |
| Drill Hole Diameter        | d <sub>o</sub>      | mm    | 10 / 12                         | 12 / 14           | 14 / 16           | 18  | 20  | 25                                | 30 / 32           | 30 / 32           | 35  | 40  |
| Minimum Embedment Depth    | h <sub>ef,min</sub> |       | 60                              | 60                | 70                | 75  | 80  | 90                                | 96                | 100               | 112 | 128 |
| Maximum Embedment Depth    | h <sub>ef,max</sub> |       | 160                             | 200               | 240               | 280 | 320 | 400                               | 480               | 500               | 560 | 640 |
| Minimum Concrete Thickness | h <sub>min</sub>    |       | h <sub>ef</sub> + 30mm (≥100mm) |                   |                   |     |     | h <sub>ef</sub> + 2d <sub>o</sub> |                   |                   |     |     |
| Minimum Edge Distance      | c <sub>min</sub>    |       | 35                              | 40                | 45                | 50  | 50  | 60                                | 70                | 70                | 75  | 85  |
| Minimum Spacing            | s <sub>min</sub>    |       | 40                              | 50                | 60                | 70  | 75  | 95                                | 120               | 120               | 130 | 150 |

1) Both nominal drill hole diameters can be used

Table 6: EP-XP Pure Epoxy - Design Resistance - Single Anchor, No Concrete Edge or Spacing Influence, 100 years working life

| Description                | Symbol    | Units | Ø8   | Ø10   | Ø12  | Ø14  | Ø16  | Ø20  | Ø24   | Ø25   | Ø28   | Ø32   |
|----------------------------|-----------|-------|------|-------|------|------|------|------|-------|-------|-------|-------|
| Embedment Depth            | $h_{ef}$  | mm    | 80   | 90    | 110  | 130  | 160  | 180  | 200   | 220   | 300   | 450   |
| Minimum Concrete Thickness | $h_{min}$ |       | 110  | 120   | 140  | 166  | 200  | 230  | 260   | 280   | 370   | 530   |
| NON-CRACKED CONCRETE       |           |       |      |       |      |      |      |      |       |       |       |       |
| TENSION                    | $N_{Rd}$  | kN    | 19.3 | 28.6  | 42.3 | 54.3 | 74.2 | 88.5 | 103.7 | 119.6 | 190.5 | 316   |
| SHEAR                      | $V_{Rd}$  |       | 9.2  | 14.4  | 20.7 | 28.2 | 36.9 | 57.6 | 82.9  | 90    | 112.9 | 147.4 |
| CRACKED CONCRETE           |           |       |      |       |      |      |      |      |       |       |       |       |
| TENSION                    | $N_{Rd}$  | kN    | 8.44 | 12.53 | 23.5 | 32.4 | 45.5 | 61.9 | 72.6  | 83.7  | 133.3 | 245   |
| SHEAR                      | $V_{Rd}$  |       | 9.2  | 14.4  | 20.7 | 28.2 | 36.9 | 57.6 | 82.9  | 90    | 112.9 | 147.4 |
| SEISMIC C1 CATEGORY        |           |       |      |       |      |      |      |      |       |       |       |       |
| TENSION                    | $N_{Rd}$  | kN    | 8.4  | 12.5  | 23.5 | 32.3 | 44.1 | 52.6 | 61.7  | 71.1  | 113.3 | 208.2 |
| SHEAR                      | $V_{Rd}$  |       | 6.5  | 10.1  | 14.5 | 19.8 | 25.8 | 40.3 | 58.1  | 63    | 79    | 103.2 |

1) Concrete strength is C20/25, f<sub>ck,cube</sub> = 25 N/mm<sup>2</sup> unreinforced, hammer drilling (HD) and CD, hole condition is "dry", temperature range 24°C long-term/40°C short-term.

2) Tabulated loads are valid at critical spacing and critical edge distance only.

3) Nominal tensile strength (f<sub>uk</sub>) is determined by the equation: f<sub>uk</sub> = 550 MPa x A<sub>nom</sub>

4) All design resistances are derived from the product's ETA (European Technical Assessment ETA-25/0483). For combined tension and shear loads or anchor groups, spacing and edge distance influence, a calculation per EAD 330499 shall be done. Simpson Strong-Tie® Anchor Designer™ for Concrete Software used for analysis.

5) Tabulated loads for C1 category are for a working life of 50 years.


6) Factor for annular gap a = 1.0

Table 7: EP-XP Pure Epoxy - Rebar Design Resistance

| Description                 | Symbol            | Units | Ø8   | Ø10  | Ø12  | Ø14  | Ø16  | Ø20   | Ø24   | Ø25   | Ø28   | Ø32   |
|-----------------------------|-------------------|-------|------|------|------|------|------|-------|-------|-------|-------|-------|
| Design Resistance - TENSION | N <sub>Rd,s</sub> | kN    | 19.7 | 30.9 | 44.4 | 60.5 | 79.0 | 123.4 | 177.7 | 192.8 | 241.9 | 316.0 |
| Design Resistance - SHEAR   | V <sub>Rd,s</sub> |       | 9.2  | 14.4 | 20.7 | 28.2 | 36.9 | 57.6  | 82.9  | 90.0  | 112.9 | 147.4 |

## Installation

Note: Refer to ETA for additional information




**IMPORTANT:** Prior to dispensing into the anchor hole, purge a minimum of three full strokes until it shows a consistent colour.



Drill hole to specified diameter and depth.



Minimum of 2x blow / 2x brush / 2x blow (min. 6 bar)



From the bottom of the hole, fill to approx. two thirds, slowly withdrawing the nozzle to avoid air pockets.



Insert clean, oil free anchor, turning slowly until reaching the required embedment depth. Do not disturb anchor until fully cured (see curing table).

Simpson Strong-Tie® (New Zealand) Ltd

Call 09 477 4440

www.strongtie.co.nz

Simpson Strong-Tie® Australia Pty Ltd

Call 1300 STRONGTIE (1300 787 664)

www.strongtie.com.au

**Simpson Strong-Tie Limited Warranty:** For the Limited Warranty that applies to Simpson Strong-Tie products, please consult www.strongtie.com.au/warranty or www.strongtie.co.nz/warranty. To obtain a copy of the Limited Warranty, contact us at info.au@strongtie.com or info.nz@strongtie.com, or at the number provided here. The Limited Warranty contains important disclaimers, limitations and exclusions, and applies only if the products have been properly specified, installed, maintained, and used in accordance with the design limits and the structural, technical, and environmental specifications in the Simpson Strong-Tie Documentation. All future purchases of Simpson Strong-Tie products are subject to the terms of the Limited Warranty in effect as of the purchase date. This flyer reflects information available as of May 2025 and may be updated periodically.