

DCSD — Decking Screw Composite-to-Steel

Material

Carbon Steel

Finish

Quik Guard® Coating



Size: See the table below

Features & Benefits

- Inverted upper threads clear excess material to ensure the screw is seated properly and consistently
- Drill flute ejects composite material for easier installation
- Cap-Style Head prevents mushrooming and material from rising up above the deck for a smoother, clean looking installation
- Drives easily through 0.8mm–2.4mm steel without pre-drilling
- Quik Guard® Coating provides corrosion resistance for exterior and certain preservative-treated timber applications
- Available in 4 colours
- U.S. Patent 9,322,422

Applications

- Composite-to-Steel decking



Cap Head for a cleaner less noticeable fixing



Inverted Upper Threads clear excess material to ensure the screw is seated properly and consistently



Drill Flute ejects composite material for easier installation

Deck-Drive™

Specifications - Quik Drive® Collated

Model No.	Colour	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
DCSD238BRR250	Brown	10G x 60mm	16 TPI	#2 Drill Point	Carbon Steel Quik Guard® Coating	250	#2 Undersize Square Drive	BIT2SU-2-RC3
DCSD238GRR250	Grey							
DCSD238RDR250	Red							
DCSD238TNR250	Tan							

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.