

DHW — Decking Screw Hardwood-to-Softwood (Collated & Loose)

Material

305 Stainless Steel



Class 3 Mechanically Galvanised

Size: See the table below

Features & Benefits

- Compact Head for countersunk finish and discreet appearance
- Designed to penetrate the hardest timber without predrilling
- Wings on the shaft counter-bore hard timber to allow the head to countersink for clean look
- Stainless Steel has the ductility to allow for movement of timber decking

Applications

- Hardwood Decking and exterior Hardwood-to-Softwood joist
- This screw is available for both hand-drive and collated Quik Drive[®] system



Specifications - Hand-drive

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
DHWG60R250	10G x 60mm	Coarse Threads	Hardwood Drill Point	Carbon Steel Class 3 Mechanically Galvanised	250	#2 Undersize Square Drive	BIT2SU-RC10
SSDHW60R250				305 Stainless Steel		#2 Square Drive	BIT2S-2-RC3



Specifications - Quik Drive[®] Collated

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
DHWG60SA	10G x 60mm	Coarse Threads	Hardwood Drill Point	Carbon Steel Class 3 Mechanically Galvanised	1000	#2 Undersize Square Drive	BIT2SU-RC10
SSDHW60SA				305 Stainless Steel		#2 Square Drive	BIT2S-RC10

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.



Compact Head countersinks easily.



Winged Design easily bores out hardwood to allow head to countersink perfectly.



Hardwood Drill Point requires no predrilling.

Deck-Drive[™]

Quik Drive[®]