

DWP — Decking Screw Softwood-to-Softwood

Material

316 Stainless Steel



Size: See the table below.

Features & Benefits

- Box Threads design with raised-ridge technology greatly reduces driving torque, which allows you to drive more screws on a single battery charge
- 316 Stainless Steel for more corrosive environments such as coastal areas
- Specially-designed sharp point penetrates softwood timber products with ease
- 6-lobe drive helps prevent driver-bit cam-out, resulting in easier driving and longer bit life

Applications

- Softwood-to-Softwood Decking
- Docks, Boardwalks, Wharf, Jetty, Marina
- Timber Construction



T-25, 6-lobe drive reduces cam-out, making driving easier



Box Threads greatly reduce driving torque



Sharp Point easily penetrates softwood timber decking

Deck-Drive™

Specifications - Hand-drive

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
T08125WPR500	8G x 32mm	Box Threads	Sharp Point with Nibs	316 Stainless Steel	500	T-20, 6-lobe	BIT20T-2-RC3
T08162WPR250	8G x 42mm				250		
T10200WPR250	10G x 50mm				250	T-25, 6-lobe	BIT25T-2-RC3
T10200WPR1100					1100		
T10250WPR250	10G x 65mm				250		
T10250WPR1100					1100		
T10300WPR250	10G x 75mm				250	T-27, 6-lobe	BIT27T-2-RC3
T14300WPR150	14G x 75mm				150		
T14300WPR400					400		
T14400WPR150	14G x 100mm				150		
T14400WPR400					400		
T14600WPR100	14G x 150mm				100		

PLEASE NOTE: Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow the board manufacturer's recommendation where applicable. WARNINGS: Always wear PPE during installation. Corrosive environments, exposure to water, salt air, or chemicals (including some wood preservatives) may cause early failure. Click here for [Corrosion Information](#), [Important Information & General Notes](#).