

MTHG — Cement Sheet / Underlay Screw (Collated)

Material: Carbon Steel

Finish: Class 3 Mechanically Galvanised



Size: See the table below

Features & Benefits


- Trim Head with Nibs for easy countersinking
- High-Low Threads for secure holding down of underlayment to timber and steel frame
- Sharp Point for fast starts saving time on the worksite
- #2 square drive
- 18 TPI

Applications

- Cement Sheet/Underlay to Timber and Steel
- Bathroom wall underlay
- Recommended steel thickness 0.55mm–0.75mm



Trim Head with Nibs for easy countersinking



High-Low Threads for secure holding down of underlayment to timber and steel frame



Quik Drive®

Specifications - Quik Drive® Collated

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
MTHG114SA	7G x 32mm	High-Low Threads 18 TPI	Sharp Point	Carbon Steel Class 3 Mechanically Galvanised	2500	#2 Square	BIT2S-RC10

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.