

PPSD – Subfloor Screw Steel Frame

Material

Carbon Steel

Finish

Yellow Zinc



Size: See the table below

Features & Benefits

- T-25, 6-lobe deep recess reduces cam-out, making driving easier
- Rimmed Flat Head with Nibs provides clean countersinking
- The Pilot Point tip is an ideal for Timber-to-Steel fastening
- The holding power of PPSD screws reduces the gaps between the joist and subfloor that cause floor squeaks
- Optimal fastener length for 19mm to 22mm subfloor sheathing

Applications


- Timber-to-Steel
- Subfloor and sheathing to steel



T-25 6-lobe deep recess provides improved control and greatly bit life



Rimmed Flat Head with Nibs countersinks easily and provides a clean finish



Pilot Point tip ideal for subfloor to cold formed steel



Quik Drive®

Specifications - Quik Drive® Collated

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
PPSD1050SA	10G x 50mm	16 TPI	Pilot Point	Carbon Steel Yellow Zinc	2000	T-25, 6-lobe	BIT25T-2-RC3

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.