

SD — Strong-Drive® Connector Screw

Material: Carbon Steel

Finish: Mechanically Galvanised



Size: See the table below

Features & Benefits

- Specifically designed to replace nails in certain Simpson Strong-Tie® connectors, and is the only screw approved for that application
- 1/4" Hex Head reduces cam-out for easier installation
- Shank is specifically designed to match the fastener holes in Simpson Strong-Tie connectors
- Serrated Threads and Sharp Point make driving easier
- Optimised heat treating for ductility and strength

Applications

- Simpson Strong-Tie® Connectors



Head Stamp for easy screw identification



Ductility and Strength through optimised heat treating



Patented Serrated Threads and Sharp Point make driving easier



Strong-Drive®

Specifications - Hand-drive

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size
SD9112R100	#9 x 38mm	Serrated Threads	Sharp Point	Mechanically Galvanised	100	1/4" Hex Head
SD9212R100-R	#9 x 64mm					
SD10112R100	#10 x 38mm					
SD10212R100-R	#10 x 64mm					

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.