

# WSNTL — Flooring Screw (Collated)

**Material**

Carbon Steel

**Finish**

Yellow Zinc



**Size:** See the table below

**Features & Benefits**

- Twin Threads for enhanced holding power and faster driving
- Ribbed Flat Head with Nibs for countersunk finish
- Sharp Point for fast starts saving time on the worksite
- Superior holding power compared to 3.75mm nails

**Applications**


- Subfloor, Mid Floor
- Timber-to-Timber
- Timber Flooring



**Complies with AS 1860.2**  
WSNTLA2SA10,  
WSNTLA2LSA-2500



**Twin Threads** for enhanced holding power and faster driving



**Sharp Point** for fast starts saving time on the worksite



**Quik Drive**®

**Specifications - Quik Drive® Collated**

Model No.	Size	Thread	Point	Material & Finish	Box Qty	Drive Size	Replacement Bit
WSNTLA134SA	8G x 45mm	Twin Threads	Sharp Point	Carbon Steel Yellow Zinc	2000	#3 Square Drive	BIT3S-RC10

These coated fasteners possess a level of corrosion resistance that makes them suitable for use in some exterior and corrosive environments and with some preservative-treated timber. For applications in higher-exposure applications, consider Type-300 series stainless-steel fasteners for superior corrosion resistance. Bit(s) included with every box of screws. Pre-drilling and countersink may be necessary at ends, butt joints, and on applications where denser material is used. Follow board manufacturers recommendations where applicable.